

**SPECIFICATIONS – MicroTouch Control**

Construction..... 6061 Billet Aluminum  
 Display..... 16 LED Temperature Display  
 Interface..... 3 Capacitive Touch Buttons  
 Communication..... ThermaSol CAN Bus  
 Supply Voltage..... 5V DC



Square Styling

**Basic Functions:**

- Recall last steam settings
- Turn steam system on or off
- Set desired steam shower temperature
- Operate PowerFlush™ cleaning system
- Diagnostic LEDs, display troubleshooting errors codes
- Patent Pending Infrared temperature sensing
- Smooth operation with capacitive touch technology (CTT)

**Installation Notes:**

The control should be installed 60" inches from the floor of the shower, inside the shower only, and away from the steam head.

**Finish Chart:**

Select desired finish and replace XX with code.

PC = Polished Chrome	PN = Polished Nickel
SC = Satin Chrome	SN = Satin Nickel
PB = Polished Brass	BN = Black Nickel
SB = Satin Brass	AN = Antique Nickel
AB = Antique Brass	PG = Polished Gold
COP = Polished Copper	ORB = Oil Rubbed Bronze
ACOP = Antique Copper	WHT = White
MB = Matte Black	

**Product Specification:**

The user interface control shall be 3.75" x 3.75" x 0.63" in dimension. The Control shall be made from billet aluminum and includes the ability to operate and control: Smart Steam and PowerFlush™ System, using 100% networked digital technology.

**Shipping Information:**

Weight..... 4 lbs.  
 Length.....12 in.  
 Width.....12 in.  
 Height.....6 in.

**Style Information:**

The control is Modern Recessed.

The Square styling when installed is flush with wall within .10"

For any further assistance please contact ThermaSol at 800.776.0711 or [sales@thermasol.com](mailto:sales@thermasol.com)

